



**Europäisches
Patentamt**

**European
Patent Office**

**Office eur péen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02100793.5

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk



Eur päisches
Patentamt

Eur pean
Patent Office

Office européen
des brevets

Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation

Anmeldung Nr.:
Application no.: 02100793.5
Demande n°:

Anmeldetag:
Date of filing: 09/07/02
Date de dépôt:

Anmelder:
Applicant(s):
Demandeur(s):
AGFA-GEVAERT
2640 Mortsel
BELGIUM

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
Quality assessment of hard copy recorders.

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:
H04N1/407

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing:
Etats contractants désignés lors du dépôt:

AT/BG/BE/CH/CY/CZ/DE/DK/EE/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/

Bemerkungen:
Remarks:
Remarques:

- 2 -

[DESCRIPTION]

FIELD OF THE INVENTION

5 The present invention relates to quality assessment of hard copy recording systems, such as thermal recorders used in healthcare applications for example for generating a hard copy of a mammographic image.

BACKGROUND OF THE INVENTION

10 Nowadays several image acquisition systems exist that render medical images such as mammographic images in the form of digital signal representations.

15 An example of such an image acquisition system is a system based on temporary storage of the medical image such as a mammographic image on a photo-stimulable phosphor screen.

20 A digital signal representation of the medical image is obtained by scanning a screen which has been exposed to a radiation image by means of stimulating radiation, detecting light emitted by the screen upon stimulation and converting the detected light into an electric signal representation.

25 Another example of such an image acquisition system is a so-called direct radiography system wherein a radiation image is recorded by a two-dimensional array of radiation sensitive elements that, upon addressing, render a digital signal representation of the radiation image.

30 Still other examples may be envisaged.

35 For the purpose of diagnosis commonly a visible reproduction, either in the form of a hard copy or a soft copy is generated from the digital medical image.

To that end the digital signal representation of the medical image is applied to a hard copy recorder such as a thermal printer.

- 5 In case the diagnosis is performed on the hard copy image, the hard copy is attached to a viewing box for visual inspection and examination by the radiologist.

10 In order to obtain constant image quality of the hard copy recorded by a hard copy recorder, a regular evaluation of the image quality of the device is to be performed.

The relevant regulation such as the 'Mammography Quality Standard Act (MQSA)' of the Food and Drug Administration (FDA) prescribes the contents and the frequency of the measurements to be performed.

- 15 For mammographic image recording a number of reference values need to be tested before initial use of the recorder and, once these test are satisfactory, quality tests must be performed regularly. Some measurements are to be made on a daily basis, others on a weekly and on a semi-annual basis.

20 The results of the tests must be saved in order to comply inter alia with the above-mentioned MQSA.

The prior art test method generally consists of three major steps: printing a test pattern, measuring certain values on the printed
25 test pattern, evaluating the measured values relative to reference values.

Commonly after installation of the recorder and before initial use, a test procedure is performed to generate base line values for
30 further follow up. These values must also be determined again after total overhaul and major repair.

The daily measurements comprise : measurement of fog density, mid density, maximum density and density difference between two
35 predefined values.

- 4 -

The weekly evaluations comprise a visual test under controlled conditions following a prescribed procedure. According to this test the visibility of a number of white dots situated in a black background is tested.

5

The monthly test comprises geometric measurements, i.e. length of edges of a printed rectangular need to be measured.

10 It is also possible to calculate certain values from measured values.

Next, according to the prior art method, the measured and/or calculated values are copied onto so-called quality control charts. In addition to the measured values the following data regarding the test conditions are also to be filled out:

15

type and serial number of the mammographic system, type and serial number of the recorder, target maximum density during calibration, type and emulsion number of the recording material, type and serial number of external densitometer.

20

Finally the measured values are compared with preset limits. If the measured values do not reach a preset minimum limit or exceed a preset maximum limit, suitable measures are taken. The action must be documented.

25

The above-described daily test procedure takes a lot of time, it is estimated that about 30 minutes per day are spent in performing the daily test procedure.

Furthermore, the test procedure requires the intervention of a trained operator who is acquainted with the procedure to be performed.

30

The operator needs to be present at the location of the recorder. He needs to perform a number of manual operations. Such a method is time-consuming and error prone.

35

It is an aspect of the present invention to provide a quality assessment method and system that overcomes the prior art disadvantages.

5 SUMMARY OF THE INVENTION

The present invention provides a method as set out in claim 1. Another aspect of the invention relates to an apparatus as set out in the claims.

10

Specific features for preferred embodiments of the invention are set out in the dependent claims.

15

The quality of the reproduction characteristics of the recorder is assessed by generating a hard copy test image by means of the recorder and by measuring test values on the hard copy test image. The measured test values can then be compared with predefined limits and a corrective measure is performed if a measured test value exceeds a predefined maximum limit or is smaller than a predefined minimum limit.

20

25

According to the present invention the hard copy is generated by initiating a test print procedure on the recorder, this procedure can be initiated via a remote PC or via the recorder itself. The test print procedure comprises the steps of

- (1) retrieving from a memory a digital signal representation of a test image,
- (2) controlling the recorder to generate a hard copy corresponding with said digital signal representation of said test image.

30

The test print procedure can be initiated on the recorder itself or can be initiated from a remote personal computer.

35

In the context of the present invention a test image is an image that comprises items that need to be measured for evaluating the reproduction quality of a hard copy recorder.

- 6 -

In practice such a test image needs to enable measurement of the characteristics prescribed by the relevant regulation such as MQSA in case of mammography.

5 Commonly such a test image comprises area onto which a specific, predefined density values are to be printed such as fog density, maximum density etc.

According to the present invention, the recorder is controlled by means of digital values corresponding with the predefined density
10 values in order to reproduce predefined density values on predefined locations.

By measuring the reproduced density and by comparing this value with predefined limits surrounding the envisaged density value, the reproduction quality of the recorder is assessed.

15 Apart from density values the test image may also comprise other items such as geometric figures which permit to evaluate the geometric reproduction quality of the recorder. For example a rectangular may be provided on the test image.

20 Still other items are possible such as collections of very fine dots, the reproduction of which can be tested.

The reproduced density values are measured for example by means of a
25 densitometer which is external to the recorder.

In a specific embodiment of the present invention a densitometer is situated inside the recorder and is arranged to measure density values on the hard copy image of the test image.

This embodiment is advantageous for the following reasons.

30 No operator intervention is required for performing the measurement so that it becomes possible to economize on manpower.

Furthermore the same densitometer is used for every test procedure on a specific recorder and the same type of densitometer can be used on all recorders of the same type so that measurements are made more
35 uniform and so that comparisons can be more easily performed.

The operation will can be performed faster and is less error prone.

The method of the present invention is furthermore advantageous since the fact that the test image is stored in digital form and the measurements are performed 'on-line' in the recorder, has as a consequence that no knowledge on the test procedure or of the types of measurements to be performed is required. Operator intervention is avoided.

It is also possible that a number of characteristic values are calculated within the recorder by means of a processing unit that is programmed to perform these calculations. It is also possible that these characteristic values are calculated on a remote PC connected with the recorder. Like-wise this embodiment provides less human intervention and is less error prone.

The test results can be shown on a display unit part of the recorder so that they can be copied by the operator onto a test sheet. However, less errors will occur when the recorder is programmed to generate a digital file comprising all measured and calculated values. Preferably this file also comprises identification data identifying the recorder, the recording material, the data and time of the measurement, etc.

The measured values can be compared in this processing unit part of the recorder with limits that stored in advance in a memory device part of the recorder so that the digital file comprises the measurement values situated relative to the relevant limits. Alternatively these limits can be stored on a remote PC connected to the recorder and the comparison can be performed on the remote PC.

This recorder or the remote PC can further be programmed to generate a hard copy test report reproducing the data of this file.

If the data are stored in a file, this file can be accessed via network by a remote PC. In this way the operator does not need to be present on the location where the recorder is situated.

- 8 -

The test procedure can be initiated from a remote location and the report can also be retrieved and occasionally printed on a remote location.

5 The actions that need to be performed when measured values exceed the given limits are prescribed by regulations such as MQSA. Such regulations may also prescribe that the performed actions need to be documented. In certain occasions MQSA or other regulations prescribe that the
10 recorder needs to be stopped.

In one embodiment of the present invention the recorder is arranged so that a warning is given, e.g. a visible or auditive warning, once a measured value falls outside a given limit. In alternative
15 embodiment such a warning is given by a remote PC connected to the recorder.

When certain measured values fall outside the limits stored in advance in a memory device, the recorder can be stopped by the
20 operator.

In another embodiment the recorder is controlled so that, when certain measured values fall outside the limits stored in advance in a memory device, the operation of the recorder is automatically stopped without operator intervention. Alternatively this stop can
25 be generated under control of a remote PC connected to the recorder.

In general the hard copy recorder according to the present invention thus comprises

- a memory wherein a digital signal representation of a test image
30 is stored,
- means for controlling a print head of said recorder to generate a hard copy corresponding with said digital signal representation of said test image on a recording material.

35 A particular embodiment comprises a densitometer arranged inside the recorder for measuring density values on the hard copy corresponding

with said digital signal representation of said test image.

Means for measuring other items, such as geometric quantities may be provided.

5

A particular embodiment also comprises a memory wherein limits have been stored for measured values and processing means for comparing measured values with retrieved limits.

10

Still another embodiment comprises means for generating a hard copy report and/or a digital file comprising at least said measured density values.

15

Although the present invention has been made in the context of a thermal hard copy recorder, it will be clear that the invention can also be used in connection with other types of recorders.

The invention is particularly relevant for medical mammographic image recording because of the high quality requirements in this field. It is however likewise applicable to other fields of

20

application. ■

- 10 -

[CLAIMS]

1. Method of assessing the quality of the recording characteristics
5 of a hard copy recorder comprising the steps of
 - generating a hard copy test image by means of said recorder,
 - measuring test values on said hard copy test image,**characterised** in that said hard copy test image is generated by
 - (1) retrieving from a memory a digital signal representation of a
10 test image,
 - (2) controlling the recorder to generate a hard copy
corresponding with said digital signal representation of said
test image.
- 15 2. Method according to claim 1 wherein said test values comprise
density values and wherein said density values are measured by
means of a densitometer part of the recorder.
3. Method according to claim 2 wherein a digital file is generated
20 that at least comprises the measured values.
4. A hard copy recorder comprising
 - a memory wherein a digital signal representation of a test
image is stored,
 - 25 - means for controlling the print head of said recorder to
generate a hard copy corresponding with said digital signal
representation of said test image on a recording material.
5. A hard copy recorder according to claim 4 comprising a
30 densitometer arranged inside said recorder for measuring density
values on the hard copy corresponding with said digital signal
representation of said test image.
6. A hard copy recorder according to claim 5 comprising means for
35 generating a report comprising said measured density values.

7. A hard copy recorder according to claim 6 wherein said means for generating said report are arranged to generate an electronic file comprising said report.

5 8. A thermal hard copy recorder according to any one of claims 4-7.

■

- 1 -

[ABSTRACT]

Quality assessment of hard copy recorders.

- 5 Quality of a hard copy recorder is assessed by generating a hard
copy of a test image stored in digital form. Test values can be
measured on the generated test image inside the recorder and an
image quality report can be generated on the tested recorder.

10

15

20



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 10 0793

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 599 261 A (MINNESOTA MINING & MFG) 1 June 1994 (1994-06-01) * claim 5; figure 1 * ---	1-5,8	H04N1/407
X	WO 95 31065 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE)) 16 November 1995 (1995-11-16) * the whole document * ---	1-5	
X	EP 0 269 033 A (DU PONT) 1 June 1988 (1988-06-01) * figures 1,2 * -----	1,2,4,5	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04N
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 November 2002	Examiner Isa, S
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 10 0793

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-11-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0599261	A	01-06-1994	AU 661205 B2	13-07-1995
			AU 5041693 A	09-06-1994
			BR 9304812 A	14-06-1994
			CA 2102355 A1	26-05-1994
			CN 1088003 A ,B	15-06-1994
			DE 69321075 D1	22-10-1998
			DE 69321075 T2	20-05-1999
			EP 0599261 A1	01-06-1994
			JP 6233134 A	19-08-1994
			MX 9307323 A1	30-06-1994
			US 5481657 A	02-01-1996
WO 9531065	A	16-11-1995	EP 0707771 A1	24-04-1996
			WO 9531065 A2	16-11-1995
			JP 9500514 T	14-01-1997
			US 5721623 A	24-02-1998
EP 0269033	A	01-06-1988	US 4816863 A	28-03-1989
			AU 600321 B2	09-08-1990
			AU 8165287 A	02-06-1988
			BR 8706312 A	19-07-1988
			CA 1295651 A1	11-02-1992
			DE 3777098 D1	09-04-1992
			EP 0269033 A2	01-06-1988
			HK 66792 A	11-09-1992
			JP 63246768 A	13-10-1988
			KR 9104682 B1	09-07-1991

